

DMP 331

Industrial Pressure Transmitter for Low Pressure

Stainless Steel Sensor

accuracy according to IEC 60770:
standard: 0.35 % FSO
option: 0.25 / 0.1 % FSO



Nominal pressure

from 0 ... 100 mbar up to 0 ... 60 bar

Output signals

2-wire: 4 ... 20 mA

3-wire: 0 ... 20 mA / 0 ... 10 V

others on request

Special characteristic

- ▶ perfect thermal behaviour
- ▶ excellent long term stability
- ▶ pressure port
G 1/2" flush from 100 mbar




Optional versions

- ▶ IS-version
Ex ia = intrinsically safe
for gases and dusts
- ▶ SIL 2-according to
IEC 61508 / IEC 61511
- ▶ welded pressure sensor
- ▶ customer specific versions

The pressure transmitter DMP 331 can be used in all industrial areas when the medium is compatible with stainless steel 1.4404 (316 L) or 1.4435 (316 L). Additional are different elastomer seals as well as a helium tested welded version available.

The modular concept of the device allows to combine different stainless steel sensors and electronic modules with a variety of electrical and mechanical versions. Thus a diversity of variations is created, meeting almost all requirements in industrial applications.

Preferred areas of use are

-  Plant and machine engineering
-  Environmental engineering
(water - sewage - recycling)
-  Energy industry



Input pressure range										
Nominal pressure gauge	[bar]	-1...0	0.10	0.16	0.25	0.40	0.60	1	1.6	
Nominal pressure abs.	[bar]	-	-	-	-	0.40	0.60	1	1.6	
Overpressure	[bar]	5	0.5	1	1	2	5	5	10	
Burst pressure \geq	[bar]	7.5	1.5	1.5	1.5	3	7.5	7.5	15	
Nominal pressure gauge / abs.	[bar]	2.5	4	6	10	16	25	40	60	
Overpressure	[bar]	10	20	40	40	80	80	105	105	
Burst pressure \geq	[bar]	15	25	50	50	120	120	210	210	
Vacuum resistance		$p_N \geq 1$ bar: unlimited vacuum resistance $p_N < 1$ bar: on request								
Output signal / Supply										
Standard		2-wire: 4 ... 20 mA / $V_S = 8 \dots 32 V_{DC}$					SIL-version: $V_S = 14 \dots 28 V_{DC}$			
Option IS-protection		2-wire: 4 ... 20 mA / $V_S = 10 \dots 28 V_{DC}$					SIL-version: $V_S = 14 \dots 28 V_{DC}$			
Options 3-wire		3-wire: 0 ... 20 mA / $V_S = 14 \dots 30 V_{DC}$								
		0 ... 10 V / $V_S = 14 \dots 30 V_{DC}$								
Performance										
Accuracy ¹		standard: nominal pressure < 0.4 bar:			$\leq \pm 0.50$ % FSO					
		nominal pressure ≥ 0.4 bar:			$\leq \pm 0.35$ % FSO					
		option 1: nominal pressure ≥ 0.4 bar:			$\leq \pm 0.25$ % FSO					
		option 2: for all nominal pressure ranges:			$\leq \pm 0.10$ % FSO					
Permissible load		current 2-wire: $R_{max} = [(V_S - V_{S min}) / 0.02 A] \Omega$								
		current 3-wire: $R_{max} = 240 \Omega$								
		voltage 3-wire: $R_{min} = 10 k\Omega$								
Influence effects		supply: 0.05 % FSO / 10 V					load: 0.05 % FSO / $k\Omega$			
Long term stability		$\leq \pm 0.1$ % FSO / year at reference conditions								
Response time		2-wire: ≤ 10 msec					3-wire: ≤ 3 msec			
¹ accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)										
Thermal effects (offset and span)										
Nominal pressure p_N	[bar]	-1 ... 0			< 0.40			≥ 0.40		
Tolerance band	[% FSO]	$\leq \pm 0.75$			$\leq \pm 1$			$\leq \pm 0.75$		
in compensated range	[°C]	-20 ... 85			0 ... 70			-20 ... 85		
Permissible temperatures										
Permissible temperatures		medium: -40 ... 125 °C								
		electronics / environment: -40 ... 85 °C								
		storage: -40 ... 100 °C								
Electrical protection										
Short-circuit protection		permanent								
Reverse polarity protection		no damage, but also no function								
Electromagnetic compatibility		emission and immunity according to EN 61326								
Mechanical stability										
Vibration		10 g RMS (25 ... 2000 Hz) according to DIN EN 60068-2-6								
Shock		500 g / 1 msec according to DIN EN 60068-2-27								
Materials										
Pressure port		stainless steel 1.4404 (316 L)								
Housing		stainless steel 1.4404 (316 L)								
Option compact field housing		stainless steel 1.4301 (304); cable gland M12x1.5, brass, nickel plated (clamping range 2 ... 8 mm)								
Seals		standard: FKM				options: EPDM				
		welded version ² (for $p_N \leq 40$ bar)				others on request				
Diaphragm		stainless steel 1.4435 (316 L)								
Media wetted parts		pressure port, seals, diaphragm								
² welded version only with pressure ports according to EN 837, $p_N \leq 40$ bar										
Explosion protection (only for 4 ... 20 mA / 2-wire)										
Approvals DX19-DMP 331		IBExU 10 ATEX 1068 X / IECEx IBE 12.0027X								
		zone 0: II 1G Ex ia IIC T4 Ga								
		zone 20: II 1D Ex ia IIIC T135 °C Da								
Safety technical maximum values		$U_i = 28$ V, $I_i = 93$ mA, $P_i = 660$ mW, $C_i \approx 0$ nF, $L_i \approx 0$ μ H, the supply connections have an inner capacity of max. 27 nF to the housing								
Permissible temperatures for environment		in zone 0: -20 ... 60 °C with p_{atm} 0.8 bar up to 1.1 bar								
		in zone 1 or higher: -40/-20 ... 70 °C								
Connecting cables (by factory)		cable capacitance:				signal line/shield also signal line/signal line: 160 pF/m				
		cable inductance:				signal line/shield also signal line/signal line: 1 μ H/m				


Miscellaneous	
Option SIL2 version ³	according to IEC 61508 / IEC 61511
Current consumption	signal output current: max. 25 mA signal output voltage: max. 7 mA
Weight	approx. 200 g
Installation position	any ⁴
Operational life	100 million load cycles
CE-conformity	EMC Directive: 2014/30/EU
ATEX Directive	2014/34/EU

³ only for 4 ... 20 mA / 2-wire, not in combination with accuracy 0.1 %


⁴ Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviations in the zero point for pressure ranges $p_N \leq 1$ bar.

Wiring diagrams

2-wire-system (current)



3-wire-system (current / voltage)





Pin configuration

Electrical connection	ISO 4400	Binder 723 (5-pin)	M12x1/ metal (4-pin)	Bayonet MIL-C-26482 (10-6)		compact field housing	cable colours (IEC 60757)
				2-wire	3-wire		
Supply +	1	3	1	A	A	IN +	WH (white)
Supply -	2	4	2	B	D	IN -	BN (brown)
Signal + (for 3-wire)	3	1	3	-	B	OUT +	GN (green)
Shield	ground pin	5	4	pressure port			GNYE (green-yellow)



Electrical connections (dimensions in mm)

standard





ISO 4400 (IP 65)



options




Binder series 723, 5-pin (IP 67)




M12x1, 4-pin (IP 67)




Bayonet MIL-C-26482 (10-6) (IP 67)



compact field housing (IP 67)



cable outlet with PVC cable (IP 67)⁵



cable outlet, cable with ventilation tube (IP 68)⁶


⇒ universal field housing stainless steel 1.4404 (316 L) with cable gland M20x1.5 (ordering code 880) and other versions on request

⁵ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)

⁶ different cable types and lengths available, permissible temperature depends on kind of cable


Mechanical connections (dimensions in mm)

standard




G1/2" DIN 3852
with ISO 4400

SIL- and SIL-IS-version




G1/2" DIN 3852
with ISO 4400


options




G1/2" EN 837




G1/2" DIN 3852 open port, $p_N \leq 40$ bar




G1/2" DIN 3852
with flush sensor, $p_N \leq 40$ bar




G1/4" DIN 3852



G1/4" EN 837



1/2" NPT



1/4" NPT

⇒ metric threads and other versions on request

* with electrical connection Bayonet MIL-C-26482 (10-6) increases the length of devices by 5 mm

© 2020 BDSENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code DMP 331

DMP 331

□□□ - □□□□ - □ - □ - □□□□ - □□□□ - □□□□ - □□□□

Pressure																					
	gauge	1	1	0																	
	absolute ¹	1	1	1																	
Input																					
	[bar]																				
	0.10 ¹	1	0	0	0																
	0.16 ¹	1	6	0	0																
	0.25 ¹	2	5	0	0																
	0.40	4	0	0	0																
	0.60	6	0	0	0																
	1.0	1	0	0	1																
	1.6	1	6	0	1																
	2.5	2	5	0	1																
	4.0	4	0	0	1																
	6.0	6	0	0	1																
	10	1	0	0	2																
	16	1	6	0	2																
	25	2	5	0	2																
	40	4	0	0	2																
	60	6	0	0	2																
	-1 ... 0	X	1	0	2																
	customer	9	9	9	9															consult	
Output																					
	4 ... 20 mA / 2-wire				1																
	0 ... 20 mA / 3-wire				2																
	0 ... 10 V / 3-wire				3																
	intrinsic safety 4 ... 20 mA / 2-wire				E																
	SIL2 4 ... 20 mA / 2-wire				1S																
	SIL2 with intrinsic safety 4 ... 20 mA / 2-wire				ES																
	customer				9																consult
Accuracy																					
	standard for $p_N \geq 0.4$ bar:	0.35 % FSO			3																
	standard for $p_N < 0.4$ bar:	0.50 % FSO			5																
	option 1 for $p_N \geq 0.4$ bar:	0.25 % FSO			2																
	option 2:	0.10 % FSO ²			1																
	customer				9																consult
Electrical connection																					
	male and female plug ISO 4400				1	0	0														
	male plug Binder series 723 (5-pin)				2	0	0														
	cable outlet with PVC cable (IP67) ³				T	A	0														
	cable outlet,																				
	cable with ventilation tube (IP68) ⁴				T	R	0														
	male plug M12x1 (4-pin) / metal				M	1	0														
	Bayonet MIL-C-26482 (10-6); 2 wire				B	G	0														
	Bayonet MIL-C-26482 (10-6); 3 wire				B	G	4														
	compact field housing																				
	stainless steel 1.4301 (304)				8	5	0														
	customer				9	9	9														consult
Mechanical connection																					
	G1/2" DIN 3852				1	0	0														
	G1/2" EN 837				2	0	0														
	G1/4" DIN 3852				3	0	0														
	G1/4" EN 837				4	0	0														
	G1/2" DIN 3852																				
	with flush sensor ⁵				F	0	0														
	G1/2" DIN 3852 open pressure port ⁵				H	0	0														
	1/2" NPT				N	0	0														
	1/4" NPT				N	4	0														
	customer				9	9	9														consult
Seals																					
	FKM																				
	EPDM																				
	without (welded version) ^{5,6}																				
	customer																				consult
Special version																					
	standard																				
	customer																				consult

¹ absolute pressure possible from 0.4 bar

² not in combination with SIL

³ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70°C), others on request

⁴ code TR0 = PVC cable, cable with ventilation tube available in different types and lengths

⁵ only for $p_N \leq 40$ bar

⁶ welded version only with pressure ports according to EN 837